

**SAFETY DATA SHEET**  
**HOLZOL Worktop Oil**
**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

|                            |  |
|----------------------------|--|
| <b>PRODUCT NAME</b>        | HOLZOL Worktop Oil   |
| <b>PRODUCT NO.</b>         | 7TO/00/30  |
| <b>APPLICATION</b>         | Oil finish for wood  |
| <b>SUPPLIER</b>            | Morrells Woodfinishes Ltd<br>Wellington Works<br>Mill Lane, Woodley<br>Stockport<br>England<br>SK6 1RN<br>0161 406 5300<br>0161 406 6276<br>enquiries@morrells.co.uk |
| <b>EMERGENCY TELEPHONE</b> | 0161 406 5300 DURING OFFICE HOURS  |

**2 HAZARDS IDENTIFICATION**

|                                      |  |
|--------------------------------------|--|
| <b>CLASSIFICATION (1999/45)</b>      | R66.   |
| <b>CLASSIFICATION (EC 1272/2008)</b> | Physical Not classified.<br>Health EUH066<br>Environmental Not classified. |
| <b>CONTAINS</b>                      | NAPHTHA PETROLEUM TREATED HEAVY  |

**3 COMPOSITION/INFORMATION ON INGREDIENTS**

|   |  |
|---|--|
| <b>NAPHTHA PETROLEUM TREATED HEAVY</b>                        | <b>30-60%</b>                              |
| <b>CAS-No.: 64742-48-9</b>                                    | <b>EC No.: 265-150-3</b>                   |
| Classification (EC 1272/2008)<br>EUH066<br>Asp. Tox. 1 - H304 | Classification (67/548)<br>Xn;R65.<br>R66. |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

**4 FIRST-AID MEASURES**
**INHALATION**

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

**INGESTION**

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

**SKIN CONTACT**

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

**EYE CONTACT**

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

**5 FIRE-FIGHTING MEASURES**
**EXTINGUISHING MEDIA**

This product is not flammable. Extinguish with foam, carbon dioxide or dry powder.

**SPECIAL FIRE FIGHTING PROCEDURES**

Water spray should be used to cool containers. Keep run-off water out of sewers and water sources. Dike for water control.

# HOLZOL Worktop Oil

## UNUSUAL FIRE & EXPLOSION HAZARDS

If heated, volume and pressure increases strongly, resulting in explosion of container.

## PROTECTIVE MEASURES IN FIRE

Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace.

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

### ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses. Contain spillages with sand, earth or any suitable adsorbent material.

### SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Risk of vapour concentration on the floor and in low-lying areas. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.

### STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away from heat, sparks and open flame.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

| Name                            | STD | TWA - 8 Hrs |                        | STEL - 15 Min |  | Notes |
|---------------------------------|-----|-------------|------------------------|---------------|--|-------|
| NAPHTHA PETROLEUM TREATED HEAVY | WEL | 148 ppm     | 1200 mg/m <sup>3</sup> |               |  |       |

WEL = Workplace Exposure Limit.

### PROTECTIVE EQUIPMENT



### PROCESS CONDITIONS

Use engineering controls to reduce air contamination to permissible exposure level.

### ENGINEERING MEASURES

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of vapours.

### RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

### HAND PROTECTION

Use suitable protective gloves if risk of skin contact. Protective gloves should be used if there is a risk of direct contact or splash. For prolonged or repeated skin contact use suitable protective gloves.

### EYE PROTECTION

If risk of splashing, wear safety goggles or face shield. Wear splash-proof eye goggles to prevent any possibility of eye contact.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

|                                 |             |
|---------------------------------|-------------|
| APPEARANCE                      | Liquid      |
| FLASH POINT (°C)                | >60         |
| VOLATILE ORGANIC COMPOUND (VOC) | 274 g/litre |

## 10 STABILITY AND REACTIVITY

# HOLZOL Worktop Oil

**STABILITY**

Stable under normal temperature conditions and recommended use.

**CONDITIONS TO AVOID**

Avoid excessive heat for prolonged periods of time. Avoid heat, flames and other sources of ignition.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

**11 TOXICOLOGICAL INFORMATION**

**TOXIC DOSE 1 - LD 50** 5000 mg/kg (oral rat)

**INHALATION**

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

**INGESTION**

May cause discomfort if swallowed.

**SKIN CONTACT**

Repeated exposure may cause skin dryness or cracking.

**EYE CONTACT**

Spray and vapour in the eyes may cause irritation and smarting.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

Not regarded as dangerous for the environment.

**LC 50, 96 Hrs, FISH mg/l** 8.2

**EC 50, 48 Hrs, DAPHNIA, mg/l** 4.5

**IC 50, 72 Hrs, ALGAE, mg/l** 3.1

**DEGRADABILITY**

The product is biodegradable, but it must not be discharged into drains without permission from the authorities.

**13 DISPOSAL CONSIDERATIONS****GENERAL INFORMATION**

When handling waste, consideration should be made to the safety precautions applying to handling of the product.

**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION**

**Road Transport Notes** Not Classified

**Rail Transport Notes** Not classified.

**Sea Transport Notes** Not classified.

**Air Transport Notes** Not classified.

**15 REGULATORY INFORMATION****STATUTORY INSTRUMENTS**

The Classification, Labelling and Packaging of substances and mixtures Regulations EC 1272/2008 (CLP) and amendments

**APPROVED CODE OF PRACTICE**

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

**GUIDANCE NOTES**

Workplace Exposure Limits EH40.

**16 OTHER INFORMATION**

**REVISION DATE** 17/09/2015

**REV. NO./REPL. SDS  
GENERATED** 1

**RISK PHRASES IN FULL**

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

## HOLZOL Worktop Oil

### HAZARD STATEMENTS IN FULL

EUH066 Repeated exposure may cause skin dryness or cracking.  
H304 May be fatal if swallowed and enters airways.

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.